



Barcode Printer

ZT888t



Barcode Printer Zebra ZD888t ini merupakan generasi terbaru dari model printer barcode GK888t yang merupakan printer desktop kelas menengah paling sukses. ZD888t secara kualitas sudah teruji dan bisa mendukung cetak dalam jumlah banyak setiap harinya. Software yang bisa dipakai adalah Bartender, yang akan dibagikan saat membeli ZD888t. Printer ini juga sudah support direct thermal (tanpa ribbon) dan thermal transfer (menggunakan ribbon). ZD888t juga sudah mendukung ribbon dengan ukuran 300meter.

TAMPIAN



DEPAN



SAMPING



Barcode Printer

ZD888t

KEUNGGULAN

Kualitas Terbaik

Memiliki kualitas yang dijamin terbaik. Printer ini merupakan generasi terbaru dari seri GK888t yang sudah terbukti kualitasnya.

Cetak Jumlah Banyak

Dapat mencetak dengan jumlah yang banyak

Ribbon Maksimal

Ribbon yang digunakan maksimal hingga 300 meter

Support 2 Tipe Cetak

Tipe cetak yang disupport yaitu Direct Thermal & Thermal Transfer

Physical Characteristics

Dimension	Thermal Transfer:
	10.5 L x 7.75 W x 7.5 H in. 267 L x 197 W x 191 H mm
	Direct Thermal
	8.6 L x 6.9 W x 5.9 H in. 220 L x 176 W x 151 H mm
Weight	2.5 lbs./1.1 kg

Printer Specifications

Resolution*	203 dpi/8 dots per mm
Memory	256 MB Flash; 128 MB SDRAM
Maximum Print Width	4.09 in./104 mm for 203 dpi
Maximum Print Speed	6 in./152 mm per second
Media Sensors	Movable black mark sensor, limited range from center to left side Fixed off-center gap sensor
Firmware	ZPL II; EPL 2; XML

Operating Characteristics

Operating Temp.	40° to 105° F/4.4° to 41° C
Storage Temp.	-40° to 140° F/-40° to 60° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95%
Electrical	non-condensing Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified

Operations and Accessories

Media Handling	Factory installed peeler or cutter
Communications	• Factory-installed USB and Ethernet • Factory-installed USB and Bluetooth 4.1 • Factory-installed USB 802.11ac Wi-Fi and Bluetooth 4.1
Real Time Clock	None
Keyboard Display Unit	No serial port, thus no KDU/ZKDU

Fonts/Graphics/Symbologies

Bar Code Ratios	2:1 and 3:1
1D Bar Codes	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
2D Bar Codes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
Fonts and Graphics	16 resident expandable ZPL II bitmap fonts Two resident scalable ZPL fonts Five resident expandable EPL2 fonts Native open-type font support Unicode compliant for multi-language, on demand thermal printing China units include SimSun simplified Chinese font 50 MB user available non-volatile memory, 8 MB user available SDRAM

Standard Features

- Thermal Transfer or Direct Thermal print method
- ZPL and EPL programming languages
- Single LED status indicator
- Single button for feed/pause
- USB connectivity
- OpenACCESS™ for easy media loading
- Dual-wall frame construction
- ENERGY STAR qualified
- ZebraDesigner Essentials – easy label design tool free at www.zebra.com/zebradesigner
- Two-year standard warranty

Media and Ribbon Characteristics

Maximum Label Length	39.0 in./991 mm
Media Width	1.00 in. / 25.4 mm to 4.4 in. / 112 mm
Media Roll Size	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) standard, 1.5 in. (38.1 mm)
Thickness	0.003 in. (0.08 mm) min.; 0.0075 in. (.1905 mm)max. (tear-off mode only)"
Media Types	Roll-fed or fan-fold, die cut or continuous with or without black mark, tag stock, continuous receipt paper, and wristbands
Ribbon Outside Diameter	2.6 in./ 66 mm (300 m); 1.34 in./ 34 mm (74 m)
Maximum Ribbon Length	984 ft. (300 m)
Ribbon Ratio	1:4 media to ribbon (300 m) 1:1 media to ribbon (74 m)"
Ribbon Width	1.33 in./ 33.8 mm ~ 4.3 in./ 109.2 mm
Ribbon Core I.D.	300 Meter ribbon 1 in./ 25.4 mm 74 Meter ribbon 0.5 in./ 12.7 mm

Printers Supplies

Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.

Regulatory

- IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus
- CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM

Recommended Services

Zebra Setup Utilities	Enhances out-of-the-box experience by enabling quick and easy printer configuration
ZebraDesigner Essentials	Makes designing and printing industry-standard and compliant labels simple, including fixed or variable data
Emulations	On-printer apps allow Zebra printers to use legacy languages normally associated with other printer brands

ZEBRA
Barcode Printer

ZD888t

APLIKASI PRODUK

- Penjualan Online
- Label Barang
- Supermarket
- Dan usaha lainnya

Toko

Cafe

Supermarket

Logistik