

ZT-230



Printer Barcode ZT-230 adalah seri Industrial Printer dari Zebra yang sudah mendukung cetak direct thermal (tanpa ribbon) dan thermal transfer (menggunakan ribbon). Dibangun untuk menjadikannya lebih efisien dalam operasional pencetakan, Zebra ZT-230 menawarkan fitur yang biasanya hanya ditemukan dalam produk kelas atas. Zebra ZT-230 kaya dengan fitur dan daya tahan kinerja yang handal. Kecepatan cetak ZT-230 juga tinggi sehingga sangat bisa mendukung aktivitas industri atau pabrik

TAMPILAN



DEPAN



SAMPING

 ZEBRA
Barcode Printer
ZT-230

KEUNGGULAN

Premium

Merupakan seri premium dari Zebra yang kuat dan tahan lama

Cetak Jumlah Banyak

Cocok untuk mencetak dalam jumlah yang banyak

Berkualitas

Menghasilkan cetakan yang berkualitas

PRINTER SPECIFICATIONS

Resolution	"203 dpi/8 dots per mm 300 dpi/12 dots per mm (optional)"
Memory	"128 MB SDRAM memory 128 MB on-board linear Flash memory"
Maximum Print Width	4.097104 mm
Maximum Print Speed	67152 mm per second
Media Sensors	Transmissive and reflective sensors
Print Length	203 dpi: 15773988 mm 300 dpi: 73"/1854 mm

MEDIA CHARACTERISTICS

Maximum Media Width	0.75719.4 mm to 4.507114 mm
Maximum Media Roll Size	8.0"/203 mm O.D. on a 3.0776 mm I.D. core 6.0"/1152 mm O.D. on a 1.0"/25 mm I.D. core
Thickness	0.00370.076 mm to 0.01070.25 mm
Media Types	Continuous, die-cut, notch, black mark

RIBBON CHARACTERISTICS
(Thermal-transfer option only)

Standard Length	Z1220: 9847300 m ZT230: 1,4767450 m
Width	1.57"140 mm to 4.33"7110 mm
Core	1.0725.4 mm

OPERATING CHARACTERISTICS

Environmental	Operating Temperature: • Thermal transfer = 40°F to 105°F/5° to 40°C • Direct thermal = 32°F to 105°F/0° to 40°C Operating Humidity: 20% to 85% non-condensing Storage/Transportation Temperature: -40°F to 140°F/ -40° to 60°C Storage Humidity: 5% to 85% non-condensing
Electrical	Universal auto-ranging (PFC-compliant) power supply 100-240 VAC; 47-63 Hz ENERGY STAR qualified

Agency
Approvals

IEC 60950, EN 55022 Class B,
EN 55024, EN 61000-3-2,
EN 61000-3-3
ZT220: cTUVus, CE, FCC,
ICES-003, VCCI, C-Tick, NOM,
Gost-R, BSMI, S-Mark
(Argentina), KC, CCC,
UkrSepro, SII, SABS
ZT230: cTUVus, CE, FCC,
ICES-003, VCCI, C-Tick, NOM,
Gost-R, BSMI, S-Mark
(Argentina), KC, CCC,
UkrSepro, SII, SABS

FIRMWARE

ZBI 2.0™

"Optional powerful program-
ming language that lets printers
run stand-alone applications,
connect to peripherals, and
much more."

ZPL and ZPL II®

"Zebra Programming Language
provides sophisticated label
formatting and printer control
and is compatible with all Zebra
printers."

EPL and EPL2™

"Eltron® Programming
Language with Line Mode
simplifies label formatting and
enables format compatibility
with legacy applications.
(EPL with Line Mode available
on direct thermal models only.)
(EPL available on 203 dpi
models only.)"

BARCODE SYMBOLOGIES**Linear or 1D Barcodes**

"Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN with 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code 2D Barcodes: Aztec, Codablock, PDF417, Code 49, Data Matrix,"

2D Barcodes

"Aztec, Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, MicroPDF417, TLC 39, RSS-14 (and composite)"

Fonts and Graphics

"7 bitmapped, 1 smooth-scalable (CG Triumvirate™ Bold Condensed*)
Pre-loaded Unicode™-compliant scalable fonts for EMEA character sets
International character sets supporting the following code page:
IBM® CodePage 850
Supports user-defined fonts and graphics, including custom logos
ZPL II drawing commands including boxes and lines
58 MB user available non-volatile memory storage for downloadable objects
4 MB user-available SDRAM
*Contains UFST® from Agfa Monotype Corporation"

ZEBRA
Barcode Printer

ZT-230

APLIKASI PRODUK

- Penjualan Online
- Label Barang
- Supermarket
- Dan usaha lainnya

Toko

Cafe

Supermarket

Logistik